




































































Connector type	Extras	IEC connector type						Features						Mounting					Connection								
		Inlet	Outlet	Protection class I	Protection class II	Max. pin temperature [°C]	V-Lock cord retaining	Enhanced glow wire	Fuseholder 1-pole	Fuseholder 2-pole	Switch 1-pole	Switch 2-pole	Switch illuminated	Circuit breaker	Voltage selector	Components prewired	Screw-on front	Screw-on rear	Snap-in	Drop-in	Sandwich	Quick connect	Solder terminals	Screw terminals	PCB	IDC terminals	Alternate type with line filter
 <b>6080</b> <small>new</small>	For IP54	•		C14	C18	70	•	•								•						•					
 <b>1061</b>		•		C14	C18	70												•				•	•	•			
 <b>6010</b> <b>6015</b>		•		C14		70	•											•				•	•	•	•		
 <b>6048</b>		•		C14		70	•									•	•					•	•	•			
 <b>6061</b> <b>6061-G</b>	Gold plated contacts	•		C14	C18	70	•									•						•	•	•			
 <b>GSP1</b>		•		C14	C18	70	•										•							•			
 <b>GSP2</b>		•		C14	C18	70	•	•									•	•	•	•				•			
 <b>4761</b> <small>new</small>	IP 67	•		Spez												•						•	•	•			
 <b>6110-3</b> <b>6110-4</b>		•		C16		120	•									•	•					•	•				
 <b>6120-3</b> <b>6120-5</b>		•		C16A		155										•	•					•	•				
 <b>DC11</b>		•		C14	C18	70	•	•	•	•						•	•	•				•			DC12		
 <b>DC21</b>		•		C14	C18	70	•			•	•					•								•	DC22		
 <b>KEB2</b>		•		C14		70				•	•					•	•	•				•			DC12		
 <b>6135</b>		•		C14		70	•			•	•	•						•				•					
 <b>6145</b>		•		C14		70				•	•	•				•						•			5145		
 <b>DF11</b>		•		C14	C18	70	•			•	•	•				•	•	•				•			DF12		
 <b>DG11</b> <small>new</small>	IP 67 or IP40	•		C14	C18	70	•			•	•	•				•	•	•				•			DG12		
 <b>KEA</b> <b>KEA-Print</b>		•		C14	C18	70	•	•	•	•						•	•	•				•		•	KFA		
 <b>6200</b> <b>6202</b> <b>6205</b>		•		C14		70	•	•	•	•						•	•	•				•	•		5200		
 <b>6220</b>		•		C14		70	•	•								•	•	•				•	•		5220		



Connector type	Extras	IEC connector type						Features						Mounting					Connection												
		Inlet	Outlet	Protection class I	Protection class II	Max. pin temperature [°C]	V-Lock cord retaining	Enhanced glow wire	Fuseholder 1-pole	Fuseholder 2-pole	Switch 1-pole	Switch 2-pole	Switch illuminated	Circuit breaker	Voltage selector	Components prewired	Screw-on front	Screw-on rear	Snap-in	Drop-in	Sandwich	Quick connect	Solder terminals	Screw terminals	PCB	IDC terminals	Alternate type with line filter				
<b>IEC 10 A / UL 15 A</b>																															
	5091		•	F	H	70											•									•					
	5001		•	F	H	70												•													
	4719	Shuttered, neon indication	•	F		70		•										•									•				
<b>IEC 16 A / UL 20 A</b>																															
	4798		•	C20		70	•	•									•										•			5130	
	4793		•	C20	C24	70	•	•										•									•			C20F	
	GSP4		•	C20	C24	70	•	•										•	•	•	•						•				
	1601		•	C20		70												•													
	1621		•	C20		70												•									•				
	1624		•	C20		70													•												
	1681		•	C22		155		•										•	•								•			C22F	
	EC11		•	C20	C24	70	•	•		•	•	•			•	•	•	•								•				EC12	
	6136		•	C20		70	•			•	•	•			•	•											•				
	EF11	Undervoltage release	•	C20		70	•				•	•	•		•	•	•										•				EF12
	4797		•	J	L	70	•	•										•	•								•				
	4797-5	Light pipe	•	J		70	•												•								•				
	4710	Cross & along versions	•	J		70	•													•											•
	4710-5	Light pipe	•	J		70	•													•											•
	5017		•	J		70																					•				
<b>DC power distribution up to 2.6 kW, IEC 8.8 A / 400 VDC</b>																															
	GS21	Hot Plug, IEC TS 62735-1	•	Std1		105																					•				

# Cord connectors

		Connector type		Design					Approvals												
		Plug	Connector	IEC type	Max. pin temperature [°C]	Straight	Angled	Max. wire size [mm <sup>2</sup> ]	Max. wire size [AWG]	Max. cable dia. [mm]	VDE	ENEC	UR	cUR	UL	cUL	CSA	CSAus	CCC	PSE	Australia
<b>Rewireable cord connectors IEC 10 A / UL 15 A</b>																					
	<b>4732</b>	•	E	70	•		1	18	8.5	•				•	•				•		•
	<b>4733</b>	•	E	70		•	1	18	8.5	•				•	•				•		•
	<b>4735</b>	•	E	70	•		1.5	14	10.0	•				•	•				•		•
	<b>4736</b>	•	E	70		•	1	16	10.0	•				•	•				•		•
	<b>9009</b>	•	E	70	•		1.5		8 10.0	•				•	•						
	<b>P685</b>	•	E	70		•	1	18	8.5			•				•					
	<b>4782</b>	•	C13	70	•		1 1.5	18 14	8.5 10.0	•				•	•						•
 <b>new</b>	<b>4783</b>		C13	70	•		1.5	2.08		•				•	•				•		
	<b>4785</b>	•	C13	70		•	1 1.5	18 14	8.5 10.0	•				•	•						•
	<b>4300-06</b>	•	C13	70		•	1	18	8.5	•		•				•					
 <b>new</b>	<b>4762</b>		Spez		•		1	14	10.0	•		•	•								
	<b>4781</b>	•	C15	120	•		1 1.5	18 14	8.5 10.0	•				•	•						•
	<b>4784</b>	•	C15	120		•	1 1.5	18 14	8.5 10.0	•				•	•						•
	<b>4771</b>	•	C15A	155	•		1	16	10.0	•				•	•	•			•		•
	<b>4772</b>	•	C15A	155	•		1	16	10.0	•				•	•	•	•		•		•
<b>Rewireable cord connectors IEC 16 A / UL 20 A</b>																					
	<b>4796</b>	•	I	70	•		1.5	14	10.0	•				•	•				•		•
	<b>4789</b>	•	I	70		•	1.5 1.5	16 14	8.7 10.0	•				•	•				•		•
	<b>4300.0922</b>	•	I	70	•		2.5	12	12.0					•		•					
	<b>4795</b>	•	C19	70	•		1.5	14	10.0	•				•	•				•		•
	<b>4790</b>	•	C19	70		•	1.5 1.5	16 14	8.7 10.0	•				•	•				•		•
	<b>0104U</b>	•	C19	70	•		2.5	12	13.0	•		•				•	•				
	<b>4300.0921</b>	•	C19	70	•		2.5	12	12.0					•		•					
 <b>new</b>	<b>1658</b>	•	C21	155	•		1.5	10	16.0	•				•	•				•		
 <b>new</b>	<b>1659</b>	•	C21	155		•	1.5	10	16.0	•				•	•				•		
<b>DC power distribution up to 2.6 kW, IEC 8.8 A / 400 VDC</b>																					
 <b>new</b>	<b>GP21</b>	•	Std2	105	•		1.5	1.5		•				•							

# Distribution units

						Approvals					
						ENIEC	UR	cULR	CSA	CCC	TUV
Connector type	Power input	Outlets	Number of outlets								
<b>Distribution units 10 A / UL 15 A</b>											
	<b>0712</b>	Appliance inlet C14	Appliance outlet type F	1		•	•		•	•	•
	<b>4741</b>	Appliance inlet C14	Appliance outlet type F	2							
	<b>4750</b>	Quick connect PCB or solder terminals	Appliance outlet type F	2 up to 7		•	•	•			
	<b>4751</b>	Quick connect terminals	Appliance outlet type F	2 up to 6		•	•			•	
	<b>4752</b>	Quick connect or solder terminals	Appliance outlet type F	4		•	•	•			
	<b>4754</b>	Quick connect or solder terminals	Appliance outlet type F	4	Space for another element C14	•	•	•		•	
	<b>4758</b>	Quick connect or solder terminals	Appliance outlet type F	4	Space for a 62xx inlet with fuse	•	•	•			
	<b>4747</b>	Appliance inlet C14	Appliance outlet type F	4			•	•		•	
	<b>4748</b>	Power supply cord	Appliance outlet type F	4	Different main plugs available						
	<b>4740</b>	Appliance inlet C14 or power supply cord	Appliance outlet type F	5 or 6	Optional: switch, fuse-holder or linefilter						
	<b>FLBB</b>	Power supply cord	EU socket outlets	5	With line-filter and line-switch						

## Web Information

At [schurter.com](http://schurter.com) you can enter the connector type (e.g. 6610) into the search box and download the data sheets containing all relevant details.

## Customized solutions

In addition to its broad product range, SCHURTER also offers individual services to fulfill all customer requirements.

We will build specific samples and provide you with your customized solution. [schurter.com/connectors](http://schurter.com/connectors)